


FLEXIBLE SOLAR PANEL

SP500W-50M



ELECTRICAL DATA

Model Type	SP500W-50M
Peak Power(Pmax)	500
Maximum Power Voltage(Vmp)	56.31V
Maximum Power Current(Imp)	8.88A
Open Circuit Voltage(Voc)	66.39V
Short Circuit Current(Isc)	9.39A
Module Efficiency(%)	20.21
* STC: irradiance 1000 W/m2, AM 1.5G, and cell temperature of 25°C	

THERMAL CHARACTERISTICS & OPERATING CONDITIONS

Maximum System Voltage(V)	1500
Maximum Series Fuse Rating(A)	15
Power Tolerance	0~+3%
Pmax Temperature Coefficients(W/°C)	-0.400%
Voc Temperature Coefficients(V/°C)	-0.330%
Isc Temperature Coefficients(A/°C)	+0.048%
NOCT Nominal Operating Cell Temperature(°C)	45±2
Operating and Storage Temperature(°C)	-40~+85

MECHANICAL CHARACTERISTICS

Cell Type	210*105Mono
No. of Cells	100(10*10)
Dimensions	2158*1130*3mm
Weight	9.03kg
Junction box	IP65/IP67
Output cables	4mm² cable 90cm + mc4
MaxWind Load/Snow Load	2400Pa/5400Pa

CONTACT US >

Sunpal Power Co.,Ltd.

Email: sales38@sunpalpower.com

Phone/WhatsApp/Wechat:+86 13696791434

