

Product Features



Unique Design

New wall mount design.



LED Display

SOC, Battery status.



Flexible Capacity

Max.15pcs in parallel to extend capacity.



Safe & Reliable

Lithium iron phosphate (LFP) cell.



Easy Installation

Quick plug in +/- and parallel connection.





POWERPAL-Y4



Product Sepecifications		
Model	PP-Y4-15kWh	
Rated Voltage	51.2V	
Rated Capacity(C5)	280Ah	314Ah
Battery Cell	3.2V 280Ah Prismatic Battery Cell	3.2V 314Ah Prismatic Battery Cell
Configuration	16S1P	
Parallel Capacity	Yes,15units maximum	
Max.Charge Current/3s	200A	200A
Continuous Discharge Current	140A	157A
Discharge Cut-off Protect Voltage	44.8V	
Charge Cut-off Protect Voltage	57.6V	
Cycle Life	6000 cycles@90%DOD,0.2C,SOH80%	
Communication Port	Can,RS485,RS232	
L*W*H(mm)	660*820*239	
Weight(kg)	122kg	125kg
Protection Rating	IP21(Indoor)	
Installation	Wall mounted	
Discharge Temperature(°C)	-20~60	
Charge Temperature(℃)	0~55	
Lithium Battery Standard	UL1642/IEC62619/UN38.3/ROHS/CE-EMC	

Cooperative Inverter Brands























